



CUSHMAN

MODEL: HAULER 1200X
TYPE: GAS POWERED TRUCK
MODEL YEAR: 2012
Part No.: 618847



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 13 hp (9.7 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

Drive Train: Automatic, continuously variable transmission (CVT)

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

Cargo Bed: Roto-molded cross-linked polyethelene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch mechanism

PRODUCT OVERVIEW

Dimensions

Overall Length	113.0 in (287 cm)
Overall Width	48.5 in (123 cm)
Overall Height (No Canopy)	52.5 in (133 cm) (Top of steering wheel)
Overall Height (With Canopy)	77.0 in (196 cm)
Wheel Base	77.0 in (196 cm)
Front Wheel Track	38.0 in (97 cm)
Rear Wheel Track	38.5 in (98 cm)
Gnd Clearance @ Differential	5.3 in (15 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity	9.6 cu ft (0.27 m3)
Cargo Box material/capacity	Roto-molded poly/9.6 cu ft (0.27 m3)

Performance

Seating Capacity	2 Person
Dry Weight	910 lb (415 kg)
Curb Weight	950 lb (435 kg)
Bed Load Capacity	500 lb (225 kg)
Vehicle load capacity	800 lb (360 kg)
Outside Clearance Circle	22.0 ft (6.7 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	17 mph ± 0.5 mph (27.4 kph ± 0.8 kph)
Towing Capacity	500 lb (225 kg) max load

Steering & Suspension

Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	Stryker 22 x 9 - 10 Uni-Directional
Rear Tires	Stryker 22 x 9 - 10 Uni-Directional

Vehicle Power

Valve Train	Single Cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Replaceable Dry Cartridge
Lubrication	Pressurized Oil System
Oil Filter	Spin On
Cooling System	Air Cooled
Fuel Capacity	5.8 Gallon (22.0 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward - Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

Body & Chassis

Frame	Welded steel. DuraShield™ powder coat
Front Body & Finish	Injection Molded TPO
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Patriot Blue



CUSHMAN

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS:				ELECTRICAL:			
Stryker 22 x 9 - 10 Uni-directional	●			Headlights	●		
Turf Saver 20 x 10 -10 (Load Range b)		●		Unique Individual Key Switch		●	
Terra Trac 22 x 11 -10 with Polished 4-Spoke Wheels		●		LED Headlights		●	
COLORS:				Taillights		●	
Body Color - Patriot Blue	●			Brake Lights		●	
Body Color - Hunter Green		●		Turn Signals with 4-Way Flashers		●	
Body Color - Bright White		●		Strobe Light		●	
Body Color - Yellow		●		Fuel Gauge	●		
Body Color - Black		●		Horn	●		
Custom Body Color		●		Low Oil Indicator	●		
Seat Color - Tan		●		12 Volt Outlet		●	
Seat Color - Oyster		●		Heavy duty battery		●	
Seat Color - Gray	●			Hour Meter		●	
Seat Color - White		●		CE Kit		●	
Seat Color - Brown		●			●		
Seat Color - Black		●		WEATHER PROTECTION:			
HAULING & TOWING:				Sun Canopy (Top) Black			●
2 in (5 cm) Receiver (Front)		●		Canopy Handle			●
2 in (5 cm) Receiver (Rear)		●		Weather Enclosure - Black			●
1 7/8 in (48 mm) Ball (Rcvr Reqd)		●		Weather Enclosure - Gray			●
Angle (Rcvr Reqd)		●		Weather Enclosure - Green			●
Clevis (Rcvr Reqd)		●		Weather Enclosure - White			●
Angle, Drop (Rcvr Reqd)		●		Weather Enclosure - Tan			●
1 7/8 in (48 mm) Ball, Drop (Rcvr Reqd)		●		Windshield Flat			●
Clevis, Drop (Rcvr Reqd)		●		Windshield Fold Down			●
Power Dump (Electric)		●		TRANSAXLE:			
Trailer, Dump (Steel Bed)			●	Limited Slip Differential		●	
Trailer, Dump (Poly Bed)			●	VEHICLE CAB:			
Winch Receiver Mount		●		Steel Cab (Tan):			●
Aluminum Bed		●		Steel Cab (White):			●
OTHER PERFORMANCE:				Steel Cab (Non Standard Color):			●
Ash Tray		●		Beacon, Amber (Cab Required)			●
Differential Guard		●		Defroster/Fan (Cab Required)			●
Front Fascia & Brush Guard (Black)	●			Dome Light (Cab Required)			●
Glove Box Door (Locking) Driver Side		●		Doors (Steel) Tan (Cab Required)			●
Glove Box Door (Locking) Passenger Side		●		Doors (Steel) White (Cab Required)			●
Remote Air Intake		●		Doors (Steel) Non Standard Color (Cab Required)			●
State of Charge Meter		●		Doors (Vinyl) Tan (Cab Required)			●
Clays Car Field Accy			●	Rear View Mirror (Cab Required)			●
Gun Holder			●	Strobe Light (Cab Required)			●
Gun Mount Swivel			●	Windshield Wiper (Cab Required)			●
Winch		●		Curtis Cab Mirrors			●
High Altitude Jetting		●		Work Light			●
				Fuse Block			●
				Cab (without doors)			●
				Doors (Set)			●